

- 1 -

## OPTICAL PICKUP

## FIELD OF THE INVENTION

The present invention relates to optical pickups for optically reading/writing data on an optical storage medium.

## BACKGROUND OF THE INVENTION

Light-based technologies are extensively researched, with some of them already in commercial use, in various fields including communications, measurement, and fabrication to exploit their many advantages in frequency (speed), capability to handle phase and space data processing, etc.

The technology depends on a highly precise objective lens to focus a light beam. The highly precise objective lens is playing an increasingly important role in recent

development of bulk storage technology, due to an outstanding demand for light-based, image-capturing apparatus.

To develop an optical bulk data storage technology, or specifically, to develop storage media with an increased recording density, the objective lens needs to be capable of producing a sufficiently focused beam spot on the recording face of a storage medium. As conventionally known, the size of the beam spot produced by an objective lens is directly proportional to the wavelength of light and inversely proportional to the NA (Numerical Aperture) of the objective lens.

As to reduction in light beam wavelength, progress has been made as a result of recent development of blue laser diodes and blue or green SHG lasers.

The NA of the objective lens is also improving. An example is the DVD (Digital Versatile Disc) which boasts an NA of 0.6, in view of the NA of the CD (Compact Disc) as low as 0.45.

Thus, studies are going on to increase the recording density of the storage medium in both aspects: reduction in light beam wavelength and growth in objective lens's NA.

Japanese Unexamined Patent Application No. 10-123410/1998 (Tokukaihei 10-123410; published on May 15,

1998) discloses an optical pickup arranged from two objective lenses, having an NA of 0.85, which are positioned opposite to each other with a predetermined distance therebetween, to achieve a higher density.

Due to the high NA of these two lenses arranged in two separate groups (hereinafter, "double-group lenses"), adjustment needs to be made to compensate for irregularities in thickness of transmissive layers in a storage medium and correct spherical aberrations which occur in the process of multilayer recording. For example, Japanese Unexamined Patent Application No. 10-142494/1998 (Tokukaihei 10-142494; published on May 29, 1998) discloses a technique to correct spherical aberrations by varying the distance between the objective lens. Japanese Unexamined Patent Application No. 2000-131603 (Tokukai 2000-131603; published on May 12, 2000) is another example, disclosing a technique to correct spherical aberrations of an objective lens group 201 composed of lenses 201a, 201b by altering along the optical axis OA the gap between two lenses 202a, 202b constituting an aberration-correcting optical system 202 which is positioned opposite to a storage medium 200 across the objective lens group 201 as shown in Figure 27.

However, the use of double-group lenses as an

objective lens in an optical pickup give rise to following problems.

Double-group lenses are typically housed in a barrel to maintain a predetermined distance between two lens. For example, the double-group lenses disclosed in Japanese Unexamined Patent Application No. 10-123410/1998 introduced above should be positioned elaborately through complex steps when placed in a barrel or similar object to form a single entity. The positioning should be highly precise as to the lens-to-lens distance and the inclination and displacement of the lenses with respect to an optical axis and is conducted by actually transmitting a laser beam through the lenses to observe a focused beam spot and aberrations.

Resin which secures the double-group lenses to the barrel is by no means reliable, because it lacks sufficient resistance to heat and humidity and is likely to deteriorate with time and for other factors.

The optical pickup has a mechanism including a driver, termed actuator, which moves the objective lenses independently in directions both parallel and perpendicular to the optical axis for focusing and tracking purposes. The double-group objective lenses, including the barrel which holds them together, become too heavy to move at high speed, which presents an

obstacle in the pursuit of high speed reading and writing.

A possible alternative is the use of a single lens or multiple lenses cemented together with no intervening air space therebetween (hereinafter, collectively called "single-group lens") as an objective lens. The use of these kinds of lenses can address the aforementioned problems caused by the use of double-group lenses as an objective lens as well as provide a means to fabricate a lightweight, highly reliable pickup.

A problem in the use of a single-group objective lens is that the lens is subject to property deterioration due to coma aberration if the NA has a large value. Coma aberration occurs from manufacturing tolerances: errors in surface-to-surface distance, surface precision, surface tilts (inclinations), and a shift (decentration) of the objective lens. Specifically, when the NA is as low as about 0.6, the objective lens is not affected by coma aberration.

Conversely, when the single-group objective lens has a NA as high as that of the foregoing double-group objective lenses (for example, 0.85), the single-group objective lens experiences serious property deterioration due to coma aberrations caused by manufacturing tolerances.

Coma aberration is also caused by inclination of the single-group objective lens to the recording surface of the optical storage medium.

#### SUMMARY OF THE INVENTION

The present invention has an objective to offer an optical pickup, including a single-group lens as an objective lens, which allows for weight reduction and reliability enhancement even with a high NA by correcting coma aberration affects properties of the objective lens.

To achieve the objective, an optical pickup in accordance with the present invention is an optical pickup for reading/writing data and is characterized in that it includes: a convergent optical system, composed of a singlet objective lens having a NA not less than 0.75, for converging output light emitted by a light source on an optical storage medium; and an aberration-correcting optical system for correcting coma aberrations due to an inclination or shift of central axes of both surfaces of the objective lens or an inclination of the objective lens or the optical storage medium to an optical axis of the optical pickup.

According to the structure, the aberration-correcting optical system corrects those coma aberrations due to an inclination or shift of central axes of both

surfaces of the objective lens with a 0.75 or higher NA relative to the storage medium or an inclination of the objective lens or the optical storage medium to an optical axis of the optical pickup; properties deterioration is avoided which is due to coma aberrations of the objective lens.

As a result, the use of an objective lens with a NA of 0.75 or more does not cause coma aberrations that adversely affect properties. The use of this high NA, singlet objective lens in an optical pickup can deliver high resistance to temperature and humidity changes and time-related changes, and thus offers high reliability while achieving high recording density.

Further, no fabrication is required as objective lenses arranged in two separate groups, which readily allows for increased productivity and reduced cost. A small, lightweight, and highly rigid objective lens becomes available, which enables high density, high speed data reading/writing.

The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, are not in any way intended to limit the scope of the claims of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a diagram schematically showing an arrangement of an optical pickup in accordance with an embodiment of the present invention.

Figure 2 is a cross-sectional view schematically showing an optical storage medium used in an embodiment of the present invention.

Figure 3 is a diagram schematically showing an arrangement of an objective lens and an aberration-correcting optical system in the optical pickup of Figure 1.

Figure 4 is a graph showing the relationship between the thickness error and an aberration characteristic of an objective lens after correction is made using the aberration-correcting optical system in the optical pickup of Figure 1.

Figure 5 is a graph showing the relationship between the surface tilt error and an aberration characteristic of an objective lens after correction is made using the aberration-correcting optical system in the optical pickup of Figure 1.

Figure 6 is a graph showing the relationship between the surface shift error and an aberration characteristic of an objective lens after correction is made using the aberration-correcting optical system in the optical



pickup of Figure 1.

Figure 7 is a graph showing the relationship between the surface tilt error and an aberration characteristic of an objective lens after correction is made based on the inclination of an optical storage medium in the optical pickup of Figure 1.

Figure 8 is an illustration depicting a drive control mechanism for the aberration-correcting optical system in the optical pickup of Figure 1.

Figure 9 is an illustration depicting a device to correct coma aberration, which is a part of the aberration-correcting optical system in the optical pickup of Figure 1.

Figure 10 is a diagram schematically showing an arrangement of the optical pickup with the coma aberration corrected by the device in Figure 9.

Figure 11 is a diagram showing an arrangement of an objective lens and an aberration-correcting optical system in an optical pickup in accordance with an example of the embodiment.

Figure 12 is a diagram showing an arrangement of an objective lens and an aberration-correcting optical system in an optical pickup in accordance with another example of the embodiment.

Figure 13 is a diagram showing an arrangement of an

objective lens and an aberration-correcting optical system in an optical pickup in accordance with a further example of the embodiment.

Figure 14 is a diagram showing an arrangement of an objective lens and an aberration-correcting optical system in an optical pickup in accordance with yet another example of the embodiment.

Figure 15 is a diagram schematically showing an arrangement of an objective lens and an aberration-correcting optical system in an optical pickup in accordance with another embodiment of the present invention.

Figure 16 is a graph showing the relationship between the thickness error and an aberration characteristic of an objective lens after correction is made using the aberration-correcting optical system in the optical pickup of Figure 15.

Figure 17 is a graph showing the relationship between the surface tilt error and an aberration characteristic of an objective lens after correction is made using the aberration-correcting optical system in the optical pickup of Figure 15.

Figure 18 is a graph showing the relationship between the surface shift error and an aberration characteristic of an objective lens after correction is

made using the aberration-correcting optical system in the optical pickup of Figure 15.

Figure 19 is a graph showing the relationship between the surface tilt error and an aberration characteristic of an objective lens after correction is made based on the inclination of an optical storage medium in the optical pickup of Figure 15.

Figure 20 is a diagram showing an arrangement of an objective lens and an aberration-correcting optical system in an optical pickup in accordance with a further embodiment of the present invention.

Figure 21 is a cross-sectional view schematically showing an aberration-correcting hologram lens provided to an aberration-correcting optical system in the optical pickup of Figure 20.

Figure 22 is a graph showing the relationship between the thickness error and an aberration characteristic of an objective lens after correction is made using the aberration-correcting optical system in the optical pickup of Figure 20.

Figure 23 is a graph showing the relationship between the surface tilt error and an aberration characteristic of an objective lens after correction is made using the aberration-correcting optical system in the optical pickup of Figure 20.

Figure 24 is a graph showing the relationship between the surface shift error and an aberration characteristic of an objective lens after correction is made using the aberration-correcting optical system in the optical pickup of Figure 20.

Figure 25 is a graph showing the relationship between the surface tilt error and a aberration characteristic of an objective lens after correction is made based on the inclination of an optical storage medium in the optical pickup of Figure 20.

Figure 26 is an illustration depicting another example of the aberration-correcting hologram lens provided to the aberration-correcting optical system in the optical pickup of Figure 20.

Figure 27 is a diagram showing an arrangement of an objective lens and an aberration-correcting optical system in a conventional optical pickup.

#### DESCRIPTION OF THE EMBODIMENTS

##### [Embodiment 1]

The following will describe an embodiment of the present invention in reference to Figures 1-10.

Referring to Figure 1, an optical pickup in accordance with the embodiment includes a LD 1 which is a light source, a collimator lens 2, a shape-adjusting

prism 3, a polarizing splitter 4, a quarter-wave plate 5, an aberration-correcting optical system 6, an objective lens 7, a converging lens 12, a receiving section 13, and a lens holder 14, to read/write data by converging a light beam on an optical storage medium 10.

Specifically, in the optical pickup thus structured, linearly polarized laser light emitted by the LD 1 which is a light source is collimated by the collimator lens 2 and enters the shape-adjusting prism 3 which converts the intensity distribution of the laser light emitted by the LD 1 from elliptical to semi-circular.

Having the intensity distribution converted to a semi-circular shape by the shape-adjusting prism 3, the laser light is transmitted by the polarizing splitter 4, converted to a circular polarization by the quarter-wave plate 5, before entering the aberration-correcting optical system 6. The laser light is then raised by a 45 degree mirror (not shown), focused by the objective lens 7, transmitted by a transmissive layer 8 constituting the optical storage medium 10 to produce a beam spot on the recording face 9.

Referring to Figure 2, the optical storage medium 10 includes the transmissive layer 8, the recording face 9, and a substrate 11. The transmissive layer 8 has a thickness of which the central value is 0.1 mm.

The light reflected (modulated) at the recording face 9 of the optical storage medium 10 travels back the same path shown in Figure 1. Specifically, the return light is transmitted by the objective lens 7 and the aberration-correcting optical system 6, converted back to a linear polarization by the quarter-wave plate 5, turned by almost 90 degrees by the polarizing splitter 4 (because the polarization direction has been rotated by 90 degrees in the incident and return paths), transmitted by the converging lens 12 to enter the receiving section 13.

As shown in Figure 1, the objective lens 7 in the optical pickup is secured to the lens holder 14 which is in turn secured by four wires (not shown) to a housing (not shown) which is part of the optical pickup.

Now, referring to Figure 3, the following will describe an arrangement of the aberration-correcting optical system 6.

The aberration-correcting optical system 6 includes two lenses arranged in two separate groups (double-group lenses), the one closer to the LD designated a first aberration-correcting lens (element) 15, the one closer to the optical storage medium 10 designated a second aberration-correcting lens (element) 16. The first aberration-correcting lens 15 is an aspheric lens with a

negative refraction power and the second aberration-correcting lens 16 is an aspheric lens with a positive refraction power: both are made of a single lens. The first aberration-correcting lens 15 and the second aberration-correcting lens 16 are positioned on the optical axis OA of the light emitted by the LD onto the optical storage medium 10.

Table 1 shows the optical structure of the objective lens 7 and the aberration-correcting optical system 6.

The aspheric constants in Table 1 satisfy:

$$Z = (1/r)y^2 / \{1 + (1 - (1+K)(1/r)^2y^2)^{1/2}\} + Ay^4 + By^6 + Cy^8 + Dy^{10} + Ey^{12} + Fy^{14} + Gy^{16} + Hy^{18} + Jy^{20}$$

where Z is a depth measured along the optical axis with a vertex of the surface as the reference, y is a height above the optical axis, r is a paraxial curvature radius, K is a conical constant, and A, B, C, D, E, F, G, H, and J are aspheric constants.

Still referring to Table 1, surface numbers S1-S7 represent surfaces of the lenses and a face of the transmissive layer 8 of the optical storage medium 10 facing the objective lens 7, as shown in Figure 3.

TABLE. 1

	SURFACE NO.	CURVATURE RADIUS (mm)	SURFACE INTERVAL (mm)	INDEX OF REFRACTION OF GLASS	ABBE NUMBER OF GLASS
FIRST ABERRATION-CORRECTING LENS	S1	-9.43233	1.0	nd=1.51680	$\nu$ d=64.2
		K:-6.092373 A:0.164522E-02 B:0.165341E-02 C:0.237202E-02 D:-0.831718E-03			
	S2	4.96737	3.98		
SECOND ABERRATION-CORRECTING LENS	S3	-37.75778	1.0	nd=1.51680	$\nu$ d=64.2
	S4	-5.07138	5.0		
		K:-0.107492 A:0.113991E-03 B:0.756886E-04 C:0.961254E-06 D:0.453347E-05			
FOCUS	ST0	infinity	0		
OBJECTIVE LENS	S5	1.4792	2.3	nd=1.81474	$\nu$ d=37.0
		K:-0.486800 A:0.368610E-02 B:-0.131835E-03 C:0.188556E-02 D:-0.309584E-02 E:0.219847E-02 F:-0.588395E-03 G:-0.840131E-04 H:0.434856E-04 J:-0.146533E-05			
	S6	28.0979	0.44		
		K:0.000000 A:0.103679E+00 B:-0.190848E+00 C:-0.926785E-01 D:0.287996E+00 E:0.195929E+00 F:-0.393015E+00 G:-0.208769E-03 H:0.568055E-01 J:-0.117780E-03			
TRANSMISSIVE LAYER	S7	infinity	0.1	nd=1.585	$\nu$ d=29.9
	IMAGE	infinity			



The objective lens 7 is designed to receive a parallel luminous flux with a NA of 0.85 (so-called infinite conjugation) and cause substantially no aberrations when the transmissive layer 8 is 0.1 mm thick. The material has an index of refraction of 1.852 for the actually used wavelength of 410 nm.

The objective lens 7 has an effective luminous flux diameter,  $\phi$ , of 3 and a focal length of 1.763 mm.

Now, the aberration-correcting optical system 6 will be described in terms of arrangement for transmissive layers of different thicknesses.

For example, to write/read data on multilayer storage media with a 0.08 mm, 0.1 mm, and 0.12 mm thick transmissive layer 8, for example, the first aberration-correcting lens 15 and the second aberration-correcting lens 16, when separated by an appropriate distance from each other, can reduce spherical aberrations to lowest levels on the recording face 9. The distance between the center of the first aberration-correcting lens 15 and the center of the second aberration-correcting lens 16 is shown in Table 2 for the foregoing thicknesses of the transmissive layer.

TABLE. 2

THICKNESS OF TRANSMISSIVE LAYER	0.08mm	0.1mm	0.12mm
CENTER-TO-CENTER DISTANCE OF FIRST AND SECOND ABERRATION- CORRECTING LENSES	4.415mm	3.979mm	3.611mm

Now, the following will describe how to correct aberrations due to manufacturing errors of the objective lens 7.

Manufacturing tolerances of the objective lens 7 are first investigated. Taking precision in the positioning of a die in a molding process, in weight (volume) of the lens material (preform), and in fabrication of the die, etc., into consideration, the lens is likely to vary in thickness by about  $\pm 5 \mu\text{m}$ , in the shifts of both surfaces by about  $\pm 5 \mu\text{m}$ , and in the tilts of both surfaces by about  $\pm 2$  minutes; these variations are the manufacturing tolerances of the objective lens 7. Accordingly, the optical system should be designed to restrain deterioration of characteristics of the system to a minimum extent so long as errors remain within these ranges.

Meanwhile, an optical pickup can produce a

sufficiently focused, good beam if the aberration of a beam spot on the recording face 9 of the optical storage medium 10 is  $0.07\lambda$  or less in terms of the r.m.s. value of a wavefront (Marechal Criteria). To restrain aberrations within this tolerable range, tolerable aberrations for each optical component are determined; the objective lens 7 and the aberration-correcting optical system 6 should not cause an aberration exceeding about  $0.03\lambda$ . The value is treated as the specified limit.

To this end, in the pickup in accordance with the invention, the objective lens 7 is either a single lens or a singlet, and there is included the aberration-correcting optical system 6 composed of lenses (first aberration-correcting lens 15, second aberration-correcting lens 16) either one of which lenses can be tilted and shifted as well as moved along the optical axis OA. A detailed description will follow about the control of the correction of aberration of the objective lens 7 by means of driving the first and second aberration-correcting lenses 15, 16 of the aberration-correcting optical system 6.

First, spherical aberrations caused by errors in thickness of the objective lens 7 are correctable by altering the distance between the first and second aberration-correcting lenses 15, 16 of the aberration-

correcting optical system 6, or specifically, by moving either one of the lenses of the aberration-correcting optical system 6 along the optical axis OA.

Figure 4 shows raw and corrected aberrations when the thickness of the objective lens 7 contains an error within  $\pm 10 \mu\text{m}$  around the design value. The uncorrected aberration does not involve the aberration-correcting optical system 6, and the corrected aberration is obtainable as a result of altering the center-to-center distance between the first aberration-correcting lens 15 and the second aberration-correcting lens 16. It is presumed that when the objective lens 7 is molded of glass using a die as in the foregoing, the lens varies in thickness about  $\pm 5 \mu\text{m}$  due to die sealing and fabrication errors.

According to the graph in Figure 4, if no aberration-correcting optical system 6 is used (represented by a broken line in the graph), the aberration falls within the specified limit of  $0.03\lambda$  when lens thickness errors are within  $\pm 2 \mu\text{m}$ . It would be therefore understood that precision better than these figures are required in manufacture. Nevertheless, lens thickness errors less than  $\pm 2 \mu\text{m}$  are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 5 \mu\text{m}$  for the objective lens

7.

In contrast, if correction is made by altering the center-to-center distance of the first aberration-correcting lens 15 and the second aberration-correcting lens 16 (represented by a solid line in the graph), lens thickness errors as large as  $\pm 7 \mu\text{m}$  are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances of  $\pm 5 \mu\text{m}$  for the objective lens 7.

Next, coma aberrations caused by a surface tilt of the objective lens 7 (inclination of the central axes of the two surfaces of the objective lens) are correctable by shifting or tilting either one of the first aberration-correcting lens 15 and the second aberration-correcting lens 16.

Figure 5 shows raw and corrected aberrations when the surface tilt of the objective lens 7 contains an error within  $\pm 5$  minutes around the design value. The uncorrected aberration does not involve the aberration-correcting optical system 6, and the corrected aberrations are obtainable as results of altering the tilt of the first aberration-correcting lens 15 and both the tilt and shift of the first aberration-correcting lens 15 respectively. It is presumed that when the objective lens 7 is molded of glass using a die as in the

foregoing, the surface tilt varies about  $\pm 2$  minutes due to die sealing and fabrication errors.

According to the graph in Figure 5, if no aberration-correcting optical system 6 is used (represented by a broken line in the graph), the aberration falls within the specified limit of  $0.03\lambda$  when lens surface tilt errors are within  $\pm 0.5$  minutes. It would be therefore understood that precision better than these figures are required in manufacture. Nevertheless, lens surface tilt errors less than  $\pm 0.5$  minutes are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 2$  minutes for the objective lens 7.

In contrast, if correction is made by altering the tilt of the first aberration-correcting lens 15 (represented by an alternate long and short dash line in the graph), lens surface tilt errors as large as  $\pm 2.5$  minutes are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances of  $\pm 2$  minutes for the objective lens 7. Also, if correction is made by altering both the tilt and shift of the first aberration-correcting lens 15 (represented by a solid line), surface tilt errors of the objective lens 7 as large as  $\pm 5$  minutes are tolerable. These figures are again much more realistic to manufacture than

the foregoing manufacturing tolerances of  $\pm 2$  minutes for the objective lens 7.

Next, coma aberrations caused by a surface shift of the objective lens 7 (shift of the central axes of the two surfaces of the objective lens) are correctable by shifting and tilting either one of the first aberration-correcting lens 15 and the second aberration-correcting lens 16.

Figure 6 shows raw and corrected aberrations when the surface shift of the objective lens 7 contains an error within  $\pm 10 \mu\text{m}$  around the design value. The uncorrected aberration does not involve the aberration-correcting optical system 6, and the corrected aberration is obtainable as a result of altering both the tilt and shift of the first aberration-correcting lens 15. It is presumed that when the objective lens 7 is molded of glass using a die as in the foregoing, the surface shift varies about  $\pm 5 \mu\text{m}$  due to die sealing and fabrication errors.

According to the graph in Figure 6, if no aberration-correcting optical system 6 is used (represented by a broken line), the aberration falls within the specified limit of  $0.03\lambda$  when lens surface shift errors are within  $\pm 4 \mu\text{m}$ . It would be therefore understood that precision better than these figures are

required in manufacture. Nevertheless, lens surface shift errors less than  $\pm 4 \mu\text{m}$  are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 5 \mu\text{m}$  for the objective lens 7.

In contrast, if correction is made by altering both the tilt and shift of the first aberration-correcting lens 15 (represented by a solid line in the graph), lens surface shift errors as large as  $\pm 6 \mu\text{m}$  are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances  $\pm 5 \mu\text{m}$  for the objective lens 7.

Alternatively, coma aberrations caused by a surface tilt of the objective lens 7 are correctable by tilting the optical storage medium 10, for example, by tilting the axis of a motor rotating the optical storage medium 10.

Figure 7 shows raw and corrected aberrations when the surface tilt of the objective lens 7 contains an error within  $\pm 10$  minutes around the design value. The uncorrected aberration is obtainable when the optical storage medium is not inclined, and the corrected aberration is obtainable as a result of changing the inclination of the optical storage medium. It is presumed that when the objective lens 7 is molded of glass using a die as in the foregoing, the surface tilt varies about



$\pm 2$  minutes due to die sealing and fabrication errors.

According to the graph in Figure 7, if the optical storage medium 10 is not inclined (represented by a broken line), the aberration falls within the specified limit of  $0.03\lambda$  when lens surface tilt errors are within  $\pm 0.5$  minutes. It would be therefore understood that precision better than these figures are required manufacture. Nevertheless, lens surface tilt errors less than  $\pm 0.5$  minutes are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 2$  for the objective lens 7.

In contrast, if correction is made by changing the inclination of the optical storage medium 10 (represented by a solid line in the graph), surface tilt errors as large as  $\pm 7.5$  minutes are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances of  $\pm 2$  minutes for the objective lens 7.

As detailed above, the present embodiment achieves a NA as high as 0.85 with a singlet objective lens 7 by means of the inclusion of the aberration-correcting optical system 6 which corrects aberrations of the objective lens 7.

The aberration-correcting optical system 6 is adapted to address errors in thickness of the objective

lens 7, irregular thicknesses of the transmissive layer 8 of the optical storage medium 10, and multilayer recording, by rendering alterable the distance between the first aberration-correcting lens 15 with a negative refraction power and the second aberration-correcting lens 16 with a positive refraction power.

Further, the aberration-correcting optical system 6 can correct coma aberrations caused by manufacturing errors of the objective lens 7 by shifting or tilting the first aberration-correcting lens 15 or the second aberration-correcting lens 16.

The aberration-correcting optical system 6 is mounted to a driver (see Figure 8) and calculates the most suitable position of the aberration-correcting optical system 6 and controls accordingly at all times by means of jitter, envelope, or other means to detect an aberration in a reproduction signal. In other words, the aberration-correcting optical system makes it possible to detect coma aberrations caused by an inclination and distortion of the optical storage medium 10, a shift of the objective lens 7 in a direction perpendicular to the track during the tracking of the optical storage medium 10, and other factors and dynamically control the tilt or shift of the aberration-correcting optical system 6 for the most suitable properties.

Referring to Figure 8, a method will be now described of dynamically controlling the aberration-correcting optical system 6, that is, correcting (adjusting) spherical and coma aberrations during a replay of the optical storage medium 10. Figure 8 shows an optical pickup of the same structure as that of Figure 1, except that a drive control mechanism 150 is additionally provided for driving the first aberration-correcting lens 15 and the second aberration-correcting lens 16 constituting the aberration-correcting optical system 6.

The drive control mechanism 150 includes an actuator 151 on which the first aberration-correcting lens 15 is mounted and an actuator 152 on which the second aberration-correcting lens 16 is mounted.

The actuator 151 is composed of three VCMs (Voice Coil Motors) distanced by substantially equal intervals along the circumference of the first aberration-correcting lens 15. An arrangement is made to correct the tilt of the first aberration-correcting lens 15 through the control of movable amounts of the three VCMs.

Further, the actuator 152 is adapted to drive the second aberration-correcting lens 16 in a direction parallel to the optical axis OA. These arrangements renders alterable the distance between the first

aberration-correcting lens 15 and the second aberration-correcting lens 16.

The actuator 151 is connected to an actuator control circuit 153 which is in turn connected via a controller 155 to a coma aberration-correcting circuit 156. The actuator 152 is connected to an actuator control circuit 154 which is in turn connected via a controller 155 to a spherical aberration-correcting circuit 157.

The coma aberration-correcting circuit 156 and the spherical aberration-correcting circuit 157 are connected to a RF signal processing circuit 158 which is in turn connected to a receiving section 13.

For example, during a replay of the optical storage medium 10, the RF signal processing circuit 158 detects a RF signal in accordance with an optical signal detected by the receiving section 13. The RF signal is separated and fed to the coma aberration-correcting circuit 156 and the spherical aberration-correcting circuit 157. In accordance with the strength of the incoming RF signal, the first aberration-correcting lens 15 and the second aberration-correcting lens 16 are moved to suitable positions to correct the coma aberration and the spherical aberration respectively. Under these conditions, the actuator control circuits 153 and 154 transmits signals to the actuators 151 and 152 in

accordance with movements of the first aberration-correcting lens 15 and the second aberration-correcting lens 16. This enables correction of the spherical and coma aberrations even during the detection of the RF signal and thereby produces a good signal.

As to the control of the coma and spherical aberration corrections, dynamic control has been described whereby the coma and spherical aberration corrections are controlled during reading and writing of the optical storage medium 10. Static control is another control whereby the aberration-correcting optical system 6 is adjusted in advance in position upon mounting of the optical pickup and then fixed. When this is the case, it is preferable if the aberration-correcting optical system 6 is adjusted while actually observing/detecting the aberration or the shape of the beam focused by the objective lens 7. The following will describe a specific method to implement the adjustment in reference to Figure 9. The optical pickup in Figure 9 is identical to that in Figure 1, except that the former additionally includes a attitude adjusting device which adjust the attitude of the lens.

A method is now described whereby the first aberration-correcting lens 15 is adjusted using a lens adjusting mechanism to correct spherical and coma

aberrations upon mounting an optical pickup to the aberration-correcting optical system 6.

The attitude adjusting device includes a lens holder 161 holding a first aberration-correcting lens 15, an xyz stage 162 fixing the lens holder 161, an integrated lens adjusting stage 165 acting as an  $\theta_x$  stage 163 and a  $\theta_y$  stage 164, an adjustment dummy transmissive plate 166 provided on a side of the objective lens 7 where laser light leaves, an observation lens 167 allowing for observation of a spot formed by focusing laser light having been transmitted by the adjustment dummy transmissive plate 166, a CCD (Charge Coupled Device) camera 168, and a CRT monitor 169 displaying an image captured by the observation lens 167 and the CCD camera 168. The adjustment dummy transmissive plate 166 is specified to have the same thickness, i.e. 0.1 mm, of the transmissive layer 8 in the optical storage medium 10.

The attitude adjusting device thus arranged can adjust the attitude of the first aberration-correcting lens 15 by the lens holder 161 moving the first aberration-correcting lens 15 in the aberration-correcting optical system 6 linearly along the x-, y-, and z- directions shown in the figure, as well as rotating (tilted) the lens 15 in the  $\theta_x$ - and  $\theta_y$  directions.

Specifically, referring to Figure 9, laser light emitted by the LD 1 is transmitted by the collimator lens 2, the shape-adjusting prism 3, the polarizing splitter 4, the quarter-wave plate 5, the first aberration-correcting lens 15, the second aberration-correcting lens 16, the objective lens 7, and the adjustment dummy transmissive plate 166 to produce a beam spot on the surface of the observation lens 167. The shape of the beam spot is captured by the CCD camera 168 and shown on the CRT monitor 169. An observer adjusts the attitude of the first aberration-correcting lens 15 while watching the CRT monitor 169.

To adjust the attitude, the observer observes the beam spot produced by the focusing of the objective lens 7 and shown on the CRT monitor 169 with the LD 1 turned on and adjusts the first aberration-correcting lens 15 in the x-, y-,  $\theta x$ -, and  $\theta y$ -directions using the stages 162-164 of the lens adjusting stage 165 so that coma aberration is reduced as much as possible in terms of the size and shape of the spot.

Here, a quick adjustment is possible if the tilt and shift of the first aberration-correcting lens 15 and the distance between the first aberration-correcting lens 15 and the second aberration-correcting lens 16 are predicted in advance which are most suitable to correct

the residual coma aberration and the spherical aberration of the objective lens 7.

Alternatively, in stead of observing the shape of the beam spot, the wavefront aberration of the beam spot may be observed directly using a Mach-Zehnder interferometer, for example.

By adjusting the attitude of the first aberration-correcting lens 15 of the aberration-correcting optical system 6 in the x-, y-,  $\theta x$ -, and  $\theta y$ -directions to remove coma aberration in advance when the aberration-correcting optical system 6 is mounted to the optical pickup in the foregoing manner, as shown in Figure 10, the actuator 151 in Figure 8 becomes no longer necessary which tilts or shifts the first aberration-correcting lens 15.

In the optical pickup shown in Figure 10, upon reading/writing data, coma aberration is removed in advance when the aberration-correcting optical system 6 is mounted; therefore, the first aberration-correcting lens 15 is fixed while tilting (inclining) or shifting with respect to the optical axis OA. This makes is possible to remove spherical aberration for data reading/writing, by driving the actuator 152 and thus moving only the second aberration-correcting lens 16 along the optical axis OA.

By adjusting the aberration-correcting optical



system 6 using the attitude adjusting device in this manner so that coma aberration is corrected in advance, the actuator 151 and associated control circuitry shown in Figure 8 which correct coma aberration becomes no longer necessary, making the arrangement of the optical pickup simple.

In the above description, coma aberration is removed by tilting or shifting the first aberration-correcting lens 15 in advance when the aberration-correcting optical system 6 is mounted to the optical pickup. This is a mere example and there are alternatives; the second aberration-correcting lens 16 may be used to remove coma aberration.

Figure 9 shows only the first aberration-correcting lens 15 is tilted or shifted, that is, the first aberration-correcting lens 15 is driven in the x-, y-, z-,  $\theta$ x-, and  $\theta$ y-directions to correct coma aberration. This is a mere example and there are alternatives; coma aberration may be corrected by driving the second aberration-correcting lens 16 in the x-, y-, and z-directions and the first aberration-correcting lens 15 in the  $\theta$ x- and  $\theta$ y-directions or by, conversely, driving the first aberration-correcting lens 15 in the x-, y-, and z-directions and the second aberration-correcting lens 16 in the  $\theta$ x- and  $\theta$ y-directions.

Further, the actuator used in the aberration-correcting optical system 6 may be used either for the first aberration-correcting lens 15 or the second aberration-correcting lens 16. If the actuator is used in spherical aberration correction which is preceded by coma aberration correction, the actuator 152 may be provided only in the second aberration-correcting lens 16 which is not used in coma aberration correction as shown in Figure 10. Alternatively, instead of providing the actuator 152 to the second aberration-correcting lens 16, the actuator 151 may be provided only in the first aberration-correcting lens 15 to correct spherical aberration by moving the first aberration-correcting lens 15 having been used in the coma aberration correction along the optical axis OA. These members may also be arranged to work in an opposite manner.

In the present embodiment, the aberration-correcting optical system 6, used as aberration-correcting means, includes a lens (first aberration-correcting lens 15) with a negative refraction power on the side of the LD 1 and a lens (second aberration-correcting lens 16) with a positive refraction power on the side of the optical storage medium 10 to correct aberration; this is for the purpose of reducing the pickup in size. Depending on the arrangement, the optical system may include a lens with

a positive refraction power on the side of the LD 1 and a lens with a negative refraction power on the side of the optical storage medium 10 to correct aberration.

As aberration-correcting means, wavefront converting means, such as liquid crystal or a hologram, may be used. The same effects can be obtained by the combined use of wavefront converting means and the aberration-correcting optical system 6. Further, a collimator lens may double as the aberration-correcting optical system 6.

Further, in the present embodiment, an optical system in which the laser light has a wavelength of 410 nm is presented as an example. Other wavelengths may be used. The same effects are available with blue (about 400 nm) and red (650 nm) wavelengths.

Further examples of the optical pickup of the present embodiment are presented below. For convenience of description, the following will describe only those parts related to the objective lens and aberration-correcting optical system; no description is given to the other parts, since they have the same arrangement as in embodiment 1.

(Example 1)

The optical pickup of the present example includes an aberration-correcting optical system 20 and an

objective lens 21 as shown in Figure 11.

The aberration-correcting optical system 20 includes two lenses arranged in two separate groups (double-group lenses), the one closer to the LD designated a first aberration-correcting lens (element) 22, the one closer to the optical storage medium designated a second aberration-correcting lens (element) 23. The first aberration-correcting lens 22 is a spherical lens with a negative refraction power and the second aberration-correcting lens 23 is a spherical lens with a positive refraction power; both are made of a single lens. The first aberration-correcting lens 22 and the second aberration-correcting lens 23 are positioned on the optical axis OA of the light emitted by the LD onto the optical storage medium 10.

Table 3 shows the optical structure of the objective lens 21 and the aberration-correcting optical system 20. The aspheric constants are the same as those in Table 1. Further, surface numbers S1-S7 in Table 3 represent surfaces of the lenses and a face of the transmissive layer 8 of the optical storage medium 10 facing the objective lens 21, as shown in Figure 11.

TABLE. 3

	SURFACE NO.	CURVATURE RADIUS (mm)	SURFACE INTERVAL (mm)	INDEX OF REFRACTION OF GLASS	ABBE NUMBER OF GLASS
FIRST ABERRATION-CORRECTING LENS	S1	10. 85	1. 42	nd=1. 51680	$\nu$ d=64. 2
	S2	infinity	5. 365		
SECOND ABERRATION-CORRECTING LENS	S3	-17. 39	1	nd=1. 75520	$\nu$ d=27. 5
	S4	32. 65	5		
FOCUS	ST0	infinity	0		
OBJECTIVE LENS	S5	1. 4792	2. 3	nd=1. 81474	$\nu$ d=37. 0
		K:-0. 486800 A:0. 368610E-02 B:-0. 131835E-03 C:0. 188556E-02 D:-0. 309584E-02 E:0. 219847E-02 F:-0. 588395E-03 G:-0. 840131E-04 H:0. 434856E-04 J:-0. 146533E-05			
	S6	28. 0979	0. 44		
		K:0. 000000 A:0. 103679E+00 B:-0. 190848E+00 C:-0. 926785E-01 D:0. 287996E+00 E:0. 195929E+00 F:-0. 393015E+00 G:-0. 208769E-03 H:0. 568055E-01 J:-0. 117780E-03			
TRANSMISSIVE LAYER	S7	infinity	0. 1	nd=1. 585	$\nu$ d=29. 9
	IMAGE	infinity			

Downloaded from ascelibrary.org by Seattle University on 06/01/15

The objective lens 21 is designed to receive a parallel luminous flux with a NA of 0.85 (so-called infinite conjugation) and cause substantially no aberration when the transmissive layer 8 of the optical storage medium 10 is 0.1 mm thick. The material used for the objective lens 21 has an index of refraction of 1.852 for the actually used wavelength of 410 nm. The objective lens 21 has an effective luminous flux diameter,  $\phi$ , of 3 and a focal length of 1.763 mm.

The present example includes the aberration-correcting optical system 20 which corrects the aberration of the objective lens 21 to realize the singlet objective lens 21 with a NA no less than 0.85 and addresses errors in thickness of the objective lens 21, irregular thicknesses of the transmissive layer 8 of the optical storage medium 10, and multilayer recording, by rendering alterable the distance between the first aberration-correcting lens 22 with a negative refraction power and the second aberration-correcting lens 23 with a positive refraction power. Further, coma aberrations due to manufacturing errors of the objective lens 21 are correctable by shifting or tilting the first aberration-correcting lens 22 or the second aberration-correcting lens 23 during assembly.

(Example 2)

The optical pickup of the present example includes an aberration-correcting optical system 30 and an objective lens 31 as shown in Figure 12.

The aberration-correcting optical system 30 includes two lenses arranged in two separate groups (double-group lenses), the one closer to the LD designated a first aberration-correcting lens (element) 33, the one closer to the optical storage medium designated a second aberration-correcting lens (element) 34. The first aberration-correcting lens 33 is an aspheric lens with a negative refraction power and the second aberration-correcting lens 34 is an aspheric lens with a positive refraction power; both are made of a single lens. A material with a large color dispersion (Abbe constant not more than 40) is used for the first aberration-correcting lens 33. The first aberration-correcting lens 33 and the second aberration-correcting lens 34 are positioned on the optical axis OA of the light emitted by the LD onto the optical storage medium 10.

Table 4 shows the optical structure of the objective lens 31 and the aberration-correcting optical system 30. The aspheric constants are the same as those in Table 1. Further, surface numbers S1-S7 in Table 4 represent surfaces of the lenses and a face of the transmissive





TABLE. 4

	SURFACE NO.	CURVATURE RADIUS (mm)	SURFACE INTERVAL (mm)	INDEX OF REFRACTION OF GLASS	ABBE NUMBER OF GLASS
FIRST ABERRATION-CORRECTING LENS	S1	-10.97723	1	nd=1.68893	$\nu$ d=31.2
		K:-324.946662 A:0.447672E-01 B:0.957027E-02 C:0.113985E-01 D:-0.867886E-02 E:0.180116E-02			
	S2	4.10804	5.498		
		K:0.000000 A:-0.490290E-02 B:0.404106E-02 C:0.253524E-01 D:0.104942E-01 E:0.722690E-02 F:-0.436589E-10 G:-0.187935E-10 H:-0.824192E-11			
SECOND ABERRATION-CORRECTING LENS	S3	-8.28963	1.5	nd=1.58913	$\nu$ d=61.3
		K:0.000000 A:-0.149581E-03 B:-0.348942E-04 C:0.323753E-03 D:0.565503E-04			
	S4	-3.98941	5		
		K:-0.439915 A:0.111554E-02 B:0.338402E-03 C:0.516269E-04 D:-0.497864E-05 E:0.548935E-04 F:-0.119397E-04			
FOCUS	ST0	infinity	0		
OBJECTIVE LENS	S5	1.4792	2.3	nd=1.81474	$\nu$ d=37.0
		K:-0.486800 A:0.368610E-02 B:-0.131835E-03 C:0.188556E-02 D:-0.309584E-02 E:0.219847E-02 F:-0.588395E-03 G:-0.840131E-04 H:0.434856E-04 J:-0.146533E-05			
	S6	28.0979	0.44		
		K:0.000000 A:0.103679E+00 B:-0.190848E+00 C:-0.926785E-01 D:0.287996E+00 E:0.195929E+00 F:-0.393015E+00 G:-0.208769E-03 H:0.568055E-01 J:-0.117780E-03			
TRANSMISSIVE LAYER	S7	infinity	0.1	nd=1.585	$\nu$ d=29.9
	IMAGE	infinity			

The objective lens 31 is designed to receive a parallel luminous flux with a NA of 0.85 (so-called infinite conjugation) and cause substantially no aberration when the transmissive layer 8 of the optical storage medium 10 is 0.1 mm thick. The material used for the objective lens 31 has an index of refraction of 1.852 for the actually used wavelength of 410 nm. The objective lens 31 has an effective luminous flux diameter,  $\phi$ , of 3 and a focal length of 1.763 mm.

The present example includes the aberration-correcting optical system 30 which corrects the aberration of the objective lens 31 to realize the singlet objective lens 31 with a NA no less than 0.85 and addresses errors in thickness of the objective lens 31, irregular thicknesses of the transmissive layer 8 of the optical storage medium 10, and multilayer recording, by rendering alterable the distance between the first aberration-correcting lens 33 with a negative refraction power and the second aberration-correcting lens 34 with a positive refraction power. Further, coma aberrations due to manufacturing errors of the objective lens 31 are correctable by shifting or tilting the first aberration-correcting lens 33 or the second aberration-correcting lens 34 during assembly.

Further, the use of a material with an Abbe constant

of 31.2 for the first aberration-correcting lens 33 has achromatic effects and thus reduces color aberration.

(Example 3)

The optical pickup of the present example includes an aberration-correcting optical system 40 and an objective lens 41 as shown in Figure 13.

Laser light entering the aberration-correcting optical system 40 is transmitted by the objective lens 41 and enters the optical storage medium 10 to produce a beam spot on the recording face 9. The transmissive layer 8 of the optical storage medium 10 is presumed to be 0.1 mm thick.

The aberration-correcting optical system 40 includes three lenses arranged in two separate groups, the one closer to the LD designated a first aberration-correcting lens (element) 42, the one closer to the optical storage medium designated a second aberration-correcting lens (element) 43. The first aberration-correcting lens 42 is an aspheric lens with a negative refraction power and the second aberration-correcting lens 43 a spherical, achromatic doublet with a positive refraction power. The first aberration-correcting lens 42 and the second aberration-correcting lens 43 are positioned on the optical axis OA of the light emitted by the LD onto the

optical storage medium 10.

Table 5 shows the optical structure of the objective lens 41 and the aberration-correcting optical system 40. The aspheric constants are the same as those in Table 1. Further, surface numbers S1-S8 in Table 5 represent surfaces of the lenses and a face of the transmissive layer 8 of the optical storage medium 10 facing the objective lens 41, as shown in Figure 13.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216

TABLE. 5

	SURFACE NO.	CURVATURE RADIUS (mm)	SURFACE INTERVAL (mm)	INDEX OF REFRACTION OF GLASS	ABBE NUMBER OF GLASS
FIRST ABERRATION-CORRECTING LENS	S1	-69.45929	1.0	nd=1.51680	$\nu$ d=64.2
		K:-133.362033 A:0.697609E-02 B:0.663479E-03 C:-0.666027E-03 D:0.319109E-03			
	S2	3.34632	3.49		
SECOND ABERRATION-CORRECTING LENS	S3	23.48087	1	nd=1.75520	$\nu$ d=27.5
	S4	6.70534	1.5	nd=1.51680	$\nu$ d=64.2
	S5	-5.37954	5		
FOCUS	ST0	infinity	0		
OBJECTIVE LENS	S6	1.4792	2.3	nd=1.81474	$\nu$ d=37.0
		K:-0.486800 A:0.368610E-02 B:-0.131835E-03 C:0.188556E-02 D:-0.309584E-02 E:0.219847E-02 F:-0.588395E-03 G:-0.840131E-04 H:0.434856E-04 J:-0.146533E-05			
	S7	28.0979	0.44		
		K:0.000000 A:0.103679E+00 B:-0.190848E+00 C:-0.926785E-01 D:0.287996E+00 E:0.195929E+00 F:-0.393015E+00 G:-0.208769E-03 H:0.568055E-01 J:-0.117780E-03			
TRANSMISSIVE LAYER	S8	infinity	0.1	nd=1.585	$\nu$ d=29.9
	IMAGE	infinity			

The objective lens 41 is designed to receive a parallel luminous flux with a NA of 0.85 (so-called infinite conjugation) and cause substantially no aberration when the transmissive layer 8 of the optical storage medium 10 is 0.1 mm thick. The material used for the objective lens 41 has an index of refraction of 1.852 for the actually used wavelength of 410 nm. The objective lens 41 has an effective luminous flux diameter,  $\phi$ , of 3 and a focal length of 1.7625 mm.

As with embodiment 1, the aberration-correcting optical system 40 can correct spherical aberrations due to the variable thickness of the transmissive layer 8 of the optical storage medium 10 by varying the distance between the first aberration-correcting lens 42 and the second aberration-correcting lens 43 depending on the thickness of the transmissive layer 8.

Spherical aberrations due to errors in thickness and surface precision of the objective lens 41 can also be addressed by varying the distance between the first aberration-correcting lens 42 and the second aberration-correcting lens 43 in the aberration-correcting optical system 40. Coma aberrations due to shifting/tilting errors of the surface of the objective lens 41 can also be addressed by tilting the optical storage medium 10 or shifting or tilting either the first aberration-

correcting lens 42 or the second aberration-correcting lens 43 in advance during assembly. These methods of removing aberrations are the same as those in embodiment 1, which allows greater manufacturing tolerances to the objective lens 41.

Further, the use of an achromatic doublet as the second aberration-correcting lens 43 with a positive refraction power allows for reduced color aberration.

(Example 4)

The optical pickup of the present example includes an aberration-correcting optical system 50 and an objective lens 51 as shown in Figure 14.

Laser light entering the aberration-correcting optical system 50 is transmitted by the objective lens 51 and enters the optical storage medium 10 to produce a beam spot on the recording face 9. The transmissive layer 8 of the optical storage medium 10 is presumed to be 0.1 mm thick.

The aberration-correcting optical system 50 includes two lenses arranged in two separate groups (double-group lenses), the one closer to the LD designated a first aberration-correcting lens (element) 52, the one closer to the optical storage medium designated a second aberration-correcting lens (element) 53. The first

aberration-correcting lens 52 is an aspheric lens with a negative refraction power and the second aberration-correcting lens 53 is an aspheric lens with a positive refraction power; both are made of a single lens. A material with a large color dispersion (i.e., a small Abbe constant) is used for the first aberration-correcting lens 52. The first aberration-correcting lens 52 and the second aberration-correcting lens 53 are positioned on the optical axis OA of the light emitted by the LD onto the optical storage medium 10.

Table 6 shows the optical structure of the objective lens 51 and the aberration-correcting optical system 50. The aspheric constants are the same as those in Table 1. Further, surface numbers S1-S8 in Table 6 represent surfaces of the lenses and a face of the transmissive layer 8 of the optical storage medium 10 facing the objective lens 51, as shown in Figure 14.



TABLE. 6

	SURFACE NO.	CURVATURE RADIUS (mm)	SURFACE INTERVAL (mm)	INDEX OF REFRACTION OF GLASS	ABBE NUMBER OF GLASS
FIRST ABERRATION-CORRECTING LENS	S1	-10. 97723	1	nd=1. 68893	$\nu$ d=31. 2
		K:-324. 946662 A:0. 447672E-01 B:0. 957027E-02 C:0. 113985E-01 D:-0. 867886E-02 E:0. 180116E-02			
	S2	4. 10804	5. 498		
		K:0. 000000 A:-0. 490290E-02 B:0. 404106E-02 C:0. 253524E-01 D:0. 104942E-01 E:0. 722690E-02 F:-0. 436589E-10 G:-0. 187935E-10 H:-0. 824192E-11			
SECOND ABERRATION-CORRECTING LENS	S3	-8. 28963	1. 5	nd=1. 58913	$\nu$ d=61. 3
		K:0. 000000 A:-0. 149581E-03 B:-0. 348942E-04 C:0. 323753E-03 D:0. 565503E-04			
	S4	-3. 98941	5		
		K:-0. 439915 A:0. 111554E-02 B:0. 338402E-03 C:0. 516269E-04 D:-0. 497864E-05 E:0. 548935E-04 F:-0. 119397E-04			
FOCUS	ST0	infinity	0		
OBJECTIVE LENS	S5	1. 44232	1. 143	nd=1. 74330	$\nu$ d=49. 3
		K:-0. 532727 A:0. 378419E-02 B:0. 127353E-02 C:0. 159295E-02 D:-0. 338359E-02 E:0. 244551E-02 F:-0. 645421E-03 G:-0. 909806E-04 H:0. 420380E-04 J:-0. 480973E-07			
	S6	infinity	1. 199	nd=1. 75520	$\nu$ d=27. 5
	S7	-6. 92233	0. 47		
		K:0. 000000 A:0. 267390E+00 B:-0. 565493E+00 C:0. 561032E-00 D:-0. 230571E+00 E:0. 154731E-01 F:0. 119854E-14 G:0. 210943E-14 H:0. 662246E-15			
TRANSMISSIVE LAYER	S8	infinity	0. 1	nd=1. 585	$\nu$ d=29. 9
	IMAGE	infinity			

The objective lens 51 is a doublet designed to receive a parallel luminous flux with a NA of 0.85 (so-called infinite conjugation) and cause substantially no aberration when the transmissive layer 8 of the optical storage medium 10 is 0.1 mm thick. The materials used for the element closer to the LD and that closer to the optical storage medium 10 have an index of refraction of 1.76781 and 1.80304, respectively, for the actually used wavelength of 410 nm. The use of a doublet as the objective lens 51 in this manner restricts color aberrations. The objective lens 51 has an effective luminous flux diameter,  $\phi$ , of 3 and a focal length of 1.763 mm.

As with embodiment 1, the aberration-correcting optical system 50 can correct spherical aberrations due to the variable thickness of the transmissive layer 8 of the optical storage medium 10 by varying the distance between the first aberration-correcting lens 52 and the second aberration-correcting lens 53 depending on the thickness of the transmissive layer 8.

Spherical aberrations due to errors in thickness and surface precision of the objective lens 51 can also be addressed by varying the distance between the first aberration-correcting lens 52 and the second aberration-correcting lens 53 in the aberration-correcting optical

system 50. Coma aberrations due to shifting/tilting errors of the surface of the objective lens 51 can also be addressed by tilting the optical storage medium 10 or shifting or tilting either the first aberration-correcting lens 52 or the second aberration-correcting lens 53 in advance during assembly. These methods of removing aberrations are the same as those in embodiment 1, which allows greater manufacturing tolerances to the objective lens 51.

The present example includes the aberration-correcting optical system 50 which corrects the aberration of the objective lens to realize the singlet objective lens with a NA no less than 0.85 and addresses errors in thickness of the objective lens 51, irregular thicknesses of the transmissive layer 8 of the optical storage medium 10, and multilayer recording, by rendering alterable the distance between the first aberration-correcting lens 52 with a negative refraction power and the second aberration-correcting lens 53 with a positive refraction power. Further, coma aberrations due to manufacturing errors of the objective lens 51 are corrected by shifting or tilting the first aberration-correcting lens 52 or the second aberration-correcting lens 53 during assembly.

Further, the use of a material with an Abbe constant

of 31.2 for the first aberration-correcting lens 52 and the use of an achromatic doublet as the objective lens 51 allow for reduced color aberration.

In embodiment 1 and examples 1-4 above, the invention is described for a case that the objective lens has a NA of 0.85. In embodiment 2 below, the invention is described a case that the objective lens has a NA of 0.75.

[Embodiment 2]

The following will describe another embodiment of the present invention. For convenience of description, the embodiment will describe only those parts related to the objective lens and aberration-correcting optical system forming an optical pickup; no description is given to the other parts of the optical pickup, since they have the same arrangement as in embodiment 1.

The optical pickup of the present example includes an aberration-correcting optical system 60 and an objective lens 61 as shown in Figure 15.

In the optical pickup, laser light entering the aberration-correcting optical system 60 is transmitted by the objective lens 61 and enters the optical storage medium 10 to produce a beam spot on the recording face 9. The transmissive layer 8 of the optical storage medium 10

is presumed to be 0.1 mm thick.

The aberration-correcting optical system 60 includes two lenses arranged in two separate groups (double-group lenses), the one closer to the LD designated a first aberration-correcting lens (element) 62, the one closer to the optical storage medium designated a second aberration-correcting lens (element) 63. The first aberration-correcting lens 62 is an aspheric lens with a negative refraction power and the second aberration-correcting lens 63 is an aspheric lens with a positive refraction power; both are made of a single lens. The first aberration-correcting lens 62 and the second aberration-correcting lens 63 are positioned on the optical axis OA of the light emitted by the LD onto the optical storage medium 10.

Table 7 shows the optical structure of the objective lens 61 and the aberration-correcting optical system 60.

The aspheric constants in Table 7 satisfy:

$$Z = (1/r)y^2 / \{1 + (1 - (1+K)(1/r)^2y^2)^{1/2}\} + Ay^4 + By^6 + Cy^8 + Dy^{10} + Ey^{12} + Fy^{14} + Gy^{16} + Hy^{18} + Jy^{20}$$

where Z is a depth measured along the optical axis with a vertex of the surface as the reference, y is a height above the optical axis, r is a paraxial curvature radius, K is a conical constant, and A, B, C, D, E, F, G, H, and J are aspheric constants.

Still referring to Table 7, surface numbers S1-S7 represent surfaces of the lenses and a face of the transmissive layer 8 of the optical storage medium 10 facing the objective lens 61, as shown in Figure 15.

TABLE. 7

	SURFACE NO.	CURVATURE RADIUS (mm)	SURFACE INTERVAL (mm)	INDEX OF REFRACTION OF GLASS	ABBE NUMBER OF GLASS
FIRST ABERRATION- CORRECTING LENS	S1	-9.43233	1	nd=1.51680	$\nu$ d=64.2
		K:-6.092373 A:0.164522E-02 B:0.165341E-02 C:0.237202E-02 D:-0.831718E-03			
	S2	4.96737	3.98		
SECOND ABERRATION- CORRECTING LENS	S3	-37.75778	1	nd=1.51680	$\nu$ d=64.2
	S4	-5.07138	5		
		K:-0.107492 A:0.113991E-03 B:0.756886E-04 C:0.961254E-06 D:0.453347E-05			
FOCUS	ST0	infinity	0		
OBJECTIVE LENS	S5	1.56624	2	nd=1.74330	$\nu$ d=49.3
		K:-0.521909 A:0.673002E-02 B:-0.202369E-02 C:0.311717E-02 D:-0.375929E-02 E:0.204709E-02 F:-0.648953E-03 G:0.272102E-04 H:0.744195E-04 J:-0.207786E-04			
		-34.98172	0.83		
	S6	K:0.000000 A:0.150690E+00 B:-0.391056E+00 C:0.523649E+00 D:-0.354349E+00 E:0.918488E-01			
TRANSMISSIVE LAYER	S7	infinity	0.1	nd=1.585	$\nu$ d=29.9
	IMAGE	infinity			

The objective lens 61 is designed to receive a parallel luminous flux with a NA of 0.75 (so-called infinite conjugation) and cause substantially no aberration when the transmissive layer 8 of the optical storage medium 10 is 0.1 mm thick. The material used for the objective lens 61 has an index of refraction of 1.7678 for the actually used wavelength of 410 nm. The objective lens 61 has an effective luminous flux diameter,  $\phi$ , of 3 and a focal length of 2.0 mm.

As with embodiment 1, the aberration-correcting optical system 60 can correct spherical aberrations due to the variable thickness of the transmissive layer 8 of the optical storage medium 10 by varying the distance between the first aberration-correcting lens 62 and the second aberration-correcting lens 63 depending on the thickness of the transmissive layer 8.

Now, the following will describe how to correct aberrations due to manufacturing errors of the objective lens 61. Manufacturing tolerances of the objective lens 61 are first investigated. Taking precision in the positioning of a die in a molding process, in weight (volume) of the lens material (preform), and in fabrication of the die, etc., into consideration, the lens is likely to vary in thickness by about  $\pm 5 \mu\text{m}$ , in the shifts of both surfaces by about  $\pm 5 \mu\text{m}$ , and in the



tilts of both surfaces by about  $\pm 2$  minutes; these variations are the manufacturing tolerances of the objective lens 61. Accordingly, the optical system should be designed to restrain deterioration of characteristics of the system to a minimum extent so long as errors remain within these ranges.

Meanwhile, an optical pickup can produce a sufficiently focused, good beam if the aberration of a beam spot on the recording face 9 of the optical storage medium 10 is  $0.07\lambda$  or less in terms of the r.m.s. value of a wavefront (Marechal Criteria). To restrain aberrations within this tolerable range, tolerable aberrations for each optical component are determined; the objective lens 61 and the aberration-correcting optical system 60 should not cause an aberration exceeding about  $0.03\lambda$ . The value is treated as the specified limit.

To this end, in the pickup in accordance with the invention, the objective lens 61 is either a single lens or a singlet, and there is included the aberration-correcting optical system 60 composed of lenses either one of which can be tilted and shifted as well as moved along the optical axis OA.

First, spherical aberrations caused by errors in thickness of the objective lens 61 are correctable by

altering the distance between the first and second aberration-correcting lenses 62, 63 of the aberration-correcting optical system 60.

Figure 16 shows raw and corrected aberrations when the thickness of the objective lens 61 contains an error within  $\pm 20 \mu\text{m}$  around the design value. The uncorrected aberration does not involve the aberration-correcting optical system 60, and the corrected aberration is obtainable as a result of altering the center-to-center distance between the first aberration-correcting lens 62 and the second aberration-correcting lens 63. It is presumed that when the objective lens 61 is molded of glass using a die as in the foregoing, the lens varies in thickness about  $\pm 5 \mu\text{m}$  due to die sealing and fabrication errors.

According to the graph in Figure 16, if no aberration-correcting optical system 60 is used (represented by a broken line in the graph), the aberration falls within the specified limit of  $0.03\lambda$  when lens thickness errors are within  $\pm 3.5 \mu\text{m}$ . It would be therefore understood that precision better than these figures are required in manufacture. Nevertheless, lens thickness errors less than  $\pm 3.5 \mu\text{m}$  are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 5 \mu\text{m}$  for the objective lens

61.

In contrast, if correction is made by altering the center-to-center distance of the first aberration-correcting lens 62 and the second aberration-correcting lens 63 (represented by a solid line in the graph), lens thickness errors as large as  $\pm 12 \mu\text{m}$  are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances of  $\pm 5 \mu\text{m}$ .

Next, coma aberrations caused by a surface tilt of the objective lens 61 (inclination of the central axes of the two surfaces of the objective lens 61) are correctable by shifting or tilting either one of the first aberration-correcting lens 62 and the second aberration-correcting lens 63.

Figure 17 shows raw and corrected aberrations when the surface tilt of the objective lens 61 contains an error within  $\pm 10$  minutes around the design value. The uncorrected aberration does not involve the aberration-correcting optical system 60, and the corrected aberrations are obtainable as results of altering the tilt of the first aberration-correcting lens 62 and both the tilt and shift of the first aberration-correcting lens 62 respectively. It is presumed that when the objective lens 61 is molded of glass using a die as in the foregoing, the surface tilt varies about  $\pm 2$  minutes

due to die sealing and fabrication errors.

According to the graph in Figure 17, if no aberration-correcting optical system 60 is used (represented by a broken line in the graph), the aberration falls within the specified limit of  $0.03\lambda$  when lens surface tilt errors are within  $\pm 1$  minute. It would be therefore understood that precision better than these figures are required in manufacture. Nevertheless, lens surface tilt errors less than  $\pm 1$  minute are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 2$  minutes.

In contrast, if correction is made by altering the tilt of the first aberration-correcting lens 62 (represented by an alternate long and short dash line in the graph), lens surface tilt errors as large as  $\pm 4$  minutes are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances of  $\pm 2$  minutes for the objective lens 61.

Also, if correction is made by altering both the tilt and shift of the first aberration-correcting lens 62 (represented by a solid line), lens surface tilt errors as large as  $\pm 8$  minutes are tolerable. These figures are again much more realistic to manufacture than the foregoing manufacturing tolerances of  $\pm 2$  minutes.

Next, coma aberrations caused by a surface shift of

the objective lens 61 (shift of the central axes of the two surfaces of the objective lens) are correctable by shifting or tilting either one of the first aberration-correcting lens 62 and the second aberration-correcting lens 63.

Figure 18 shows raw and corrected aberrations when the surface shift of the objective lens 61 contains an error within  $\pm 10 \mu\text{m}$  around the design value. The uncorrected aberration does not involve the aberration-correcting optical system 60, and the corrected aberration is obtainable as a result of altering both the tilt and shift of the first aberration-correcting lens 62. It is presumed that when the objective lens 61 is molded of glass using a die as in the foregoing, the shifts of both surfaces of the objective lens 61 (lens surface shift errors) vary about  $\pm 5 \mu\text{m}$  due to die sealing and fabrication errors.

According to the graph in Figure 18, if no aberration-correcting optical system 60 is used (represented by a broken line), the aberration falls within the specified limit of  $0.03\lambda$  when lens surface shift errors are within  $\pm 4 \mu\text{m}$ . It would be therefore understood that precision better than these figures are required in manufacture. Nevertheless, lens surface shift errors less than  $\pm 4 \mu\text{m}$  are far from realistic to

manufacture when compared to the foregoing manufacturing tolerances of  $\pm 5 \mu\text{m}$ .

In contrast, if correction is made by altering both the tilt and shift of the first aberration-correcting lens 62 (represented by a solid line in the graph), lens surface shift errors as large as  $\pm 5.5 \mu\text{m}$  are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances  $\pm 5 \mu\text{m}$ .

Alternatively, coma aberrations caused by a surface tilt of the objective lens 61 are correctable by tilting the optical storage medium 10, for example, by tilting the axis of a motor rotating the optical storage medium 10.

Figure 19 shows raw and corrected aberrations when the surface tilt of the objective lens 61 contains an error within  $\pm 10$  minutes around the design value. The uncorrected aberration is obtainable when the optical storage medium is not inclined, and the corrected aberration is obtainable as a result of changing the inclination of the optical storage medium. It is presumed that when the objective lens 61 is molded of glass using a die as in the foregoing, the tilts of both surfaces of the objective lens 61 (lens surface tilt errors) vary about  $\pm 2$  minutes due to die sealing and fabrication errors.

According to the graph in Figure 19, if the optical storage medium 10 is not inclined (represented by a broken line), the aberration falls within the specified limit of  $0.03\lambda$  when lens surface tilt errors are within  $\pm 1$  minute. It would be therefore understood that precision better than these figures are required manufacture. Nevertheless, lens surface tilt errors less than  $\pm 1$  minute are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 2$ .

In contrast, if correction is made by changing the inclination of the optical storage medium 10 (represented by a solid line in the graph), lens surface tilt errors as large as  $\pm 6.5$  minutes are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances of  $\pm 2$  minutes for the objective lens 61.

As detailed above, the present embodiment achieves a NA as high as 0.75 with a singlet objective lens 61 by means of the inclusion of the aberration-correcting optical system 60 which corrects aberrations of the objective lens 61. The aberration-correcting optical system 60 is adapted to address errors in thickness of the objective lens 61, irregular thicknesses of the transmissive layer 8 of the optical storage medium 10, and multilayer recording, by rendering alterable the

distance between the first aberration-correcting lens 62 with a negative refraction power and the second aberration-correcting lens 63 with a positive refraction power. Further, the aberration-correcting optical system 60 can correct coma aberrations caused by manufacturing errors of the objective lens 61 by shifting or tilting the first aberration-correcting lens 62 or the second aberration-correcting lens 63.

In embodiments 1 and 2 above, the invention is described for a case when both the first and second aberration-correcting lenses forming the aberration-correcting optical system are aspheric. Alternatively, a diffraction lens may be used in place of either one of the aberration correcting lenses as in embodiment 3 below.

[Embodiment 3]

The following will describe another embodiment of the present invention. For convenience of description, the embodiment will describe only those parts related to the objective lens and aberration-correcting optical system forming an optical pickup; no description is given to the other parts of the optical pickup, since they have the same arrangement as in embodiment 1.

The optical pickup of the present example includes



an aberration-correcting optical system 70 and an objective lens 71 as shown in Figure 20.

In the optical pickup, laser light entering the aberration-correcting optical system 70 is transmitted by the objective lens 71 and enters the optical storage medium 10 to produce a beam spot on the recording face 9 of the optical storage medium 10. The transmissive layer 8 of the optical storage medium 10 is presumed to be 0.1 mm thick.

The aberration-correcting optical system 70 includes two lenses arranged in two separate groups (double-group lenses), the one closer to the LD designated an aberration-correcting lens (element) 72, the one closer to the optical storage medium designated an aberration-correcting hologram lens (element) 73. The aberration-correcting lens 72 is an aspheric lens with a negative refraction power and a focal distance of -6 mm, and the aberration-correcting hologram lens 73 is a diffraction lens (hologram lens) with a positive refraction power and a focal distance of 10.4 mm; both are made of a single lens.

The aberration-correcting hologram lens 73 has concentric grooves and its cross section forms a blaze as shown in Figure 21 to improve diffraction efficiency of first order. The aberration-correcting hologram lens 73

has a first ring pitch (cycle) of about 92  $\mu\text{m}$  and an outermost luminous flux pitch (close to circumference) of about 2.6  $\mu\text{m}$ ; the overall pitch gradually decreases from the center of the optical axis toward the circumference. The aberration-correcting hologram lens 73 is made by applying an ultraviolet-ray-setting resin on a plane glass substrate with a 2P technique and transferring the coated substrate using a die fabricated using a grounder with a diamond tool. The aberration correcting lens 72 and the aberration-correcting hologram lens 73 are positioned on the optical axis OA of the light emitted by the LD onto the optical storage medium 10.

Table 8 shows the optical structure of the objective lens 71 and the aberration-correcting optical system 70.

The aspheric constants in Table 7 satisfy:

$$Z = (1/r)y^2 / \{1 + (1 - (1+K)(1/r)^2 y^2)^{1/2}\} + Ay^4 + By^6 + Cy^8 + Dy^{10} + Ey^{12} + Fy^{14} + Gy^{16} + Hy^{18} + Jy^{20}$$

where Z is a depth measured along the optical axis with a vertex of the surface as the reference, y is a height above the optical axis, r is a paraxial curvature radius, K is a conical constant, and A, B, C, D, E, F, G, H, and J are aspheric constants.

Still referring to Table 8, surface numbers S1-S7 represent surfaces of the lenses and a face of the transmissive layer 8 of the optical storage medium 10

facing the objective lens 71, as shown in Figure 20.

TABLE. 8

	SURFACE NO.	CURVATURE RADIUS (mm)	SURFACE INTERVAL (mm)	INDEX OF REFRACTION OF GLASS	ABBE NUMBER OF GLASS
FIRST ABERRATION-CORRECTING LENS	S1	-9.43233	1.0	nd=1.51680	$\nu$ d=64.2
		K:-6.092373 A:0.164522E-02 B:0.165341E-02 C:0.237202E-02 D:-0.831718E-03			
	S2	4.96737	4.19		
SECOND ABERRATION-CORRECTING LENS	S3	infinity	1.0	nd=1.51680	$\nu$ d=64.2
		HOLOGRAM LENS			
	S4	infinity	5.0		
FOCUS	ST0	infinity	0		
OBJECTIVE LENS	S5	1.4792	2.3	nd=1.81474	$\nu$ d=37.0
		K:-0.486800 A:0.368610E-02 B:-0.131835E-03 C:0.188556E-02 D:-0.309584E-02 E:0.219847E-02 F:-0.588395E-03 G:-0.840131E-04 H:0.434856E-04 J:-0.146533E-05			
	S6	28.0979	0.44		
		K:0.000000 A:0.103679E+00 B:-0.190848E+00 C:-0.926785E-01 D:0.287996E+00 E:0.195929E+00 F:-0.393015E+00 G:-0.208769E-03 H:0.568055E-01 J:-0.117780E-03			
TRANSMISSIVE LAYER	S7	infinity	0.1	nd=1.585	$\nu$ d=29.9
	IMAGE	infinity			

The objective lens 71 is designed to receive a parallel luminous flux with a NA of 0.85 (so-called infinite conjugation) and cause substantially no aberration when the transmissive layer 8 of the optical storage medium 10 is 0.1 mm thick. The material used for the objective lens 71 has an index of refraction of 1.852 for the actually used wavelength of 410 nm. The objective lens 71 has an effective luminous flux diameter,  $\phi$ , of 3 and a focal length of 1.763 mm.

As with embodiment 1, the aberration-correcting optical system 70 can correct spherical aberrations due to the variable thickness of the transmissive layer 8 of the optical storage medium 10 by varying the distance between the aberration-correcting lens 72 and the aberration-correcting lens 73 depending on the thickness of the transmissive layer 8.

Now, the following will describe how to correct due to manufacturing errors of the objective lens 71. Manufacturing tolerances of the objective lens 71 are first investigated. Taking precision in the positioning of a die in a molding process, in weight (volume) of the lens material (preform), and in fabrication of the die, etc., into consideration, the lens is likely to vary in thickness by about  $\pm 5 \mu\text{m}$ , in the shifts of both surfaces by about  $\pm 5 \mu\text{m}$ , and in the tilts of both surfaces by

about  $\pm 2$  minutes; these variations are the manufacturing tolerances of the objective lens 71. Accordingly, the optical system should be designed to restrain deterioration of characteristics of the system to a minimum extent so long as errors remain within these ranges.

Meanwhile, an optical pickup can produce a sufficiently focused, good beam if the aberration of a beam spot on the recording face 9 of the optical storage medium 10 is  $0.07\lambda$  or less in terms of the r.m.s. value of a wavefront (Marechal Criteria). To restrain aberrations within this tolerable range, tolerable aberrations for each optical component are determined; the objective lens 71 and the aberration-correcting optical system 70 should not cause an aberration exceeding about  $0.03\lambda$ . The value is treated as the specified limit.

To this end, in the pickup in accordance with the invention, the objective lens 71 is either a single lens or a singlet, and there is included the aberration-correcting optical system 70 composed of lenses either one of which can be tilted and shifted as well as moved along the optical axis OA.

First, spherical aberrations caused by errors in thickness of the objective lens 71 are correctable by

altering the distance between the aberration-correcting lenses 72 and the aberration-correcting hologram lens 73 of the aberration-correcting optical system 70.

Figure 22 shows raw and corrected aberrations when the thickness of the objective lens 71 contains an error within  $\pm 10 \mu\text{m}$  around the design value. The uncorrected aberration does not involve the aberration-correcting optical system 70, and the corrected aberration is obtainable as a result of altering the center-to-center distance between the aberration-correcting lens 72 and the aberration-correcting hologram lens 73. It is presumed that when the objective lens 71 is molded of glass using a die as in the foregoing, the lens varies in thickness about  $\pm 5 \mu\text{m}$  due to die sealing and fabrication errors.

According to the graph in Figure 22, if no aberration-correcting optical system 70 is used (represented by a broken line in the graph), the aberration falls within the specified limit of  $0.03\lambda$  when lens thickness errors are within  $\pm 2 \mu\text{m}$ . It would be therefore understood that precision better than these figures are required in manufacture. Nevertheless, lens thickness errors less than  $\pm 2 \mu\text{m}$  are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 5 \mu\text{m}$ .

In contrast, if correction is made by altering the center-to-center distance of the aberration-correcting lens 72 and the aberration-correcting hologram lens 73 (represented by a solid line in the graph), lens thickness errors as large as  $-5\mu\text{m}$  to  $+9\mu\text{m}$  are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances of  $\pm 5 \mu\text{m}$ .

Next, coma aberrations caused by a surface tilt of the objective lens 71 (inclination of the central axes of the two surfaces of the objective lens 71) are correctable by shifting or tilting either one of the aberration correcting lens 72 and the aberration-correcting hologram lens 73.

Figure 23 shows raw and corrected aberrations when the surface tilt of the objective lens 71 contains an error within  $\pm 10$  minutes around the design value. The uncorrected aberration does not involve the aberration-correcting optical system 70, and the corrected aberrations are obtainable as results of altering the tilt of the aberration-correcting lens 72 and both the tilt and shift of the aberration-correcting lens 72 respectively. It is presumed that when the objective lens 71 is molded of glass using a die as in the foregoing, the surface tilt varies about  $\pm 2$  minutes due to die sealing and fabrication errors.

According to the graph in Figure 23, if no aberration-correcting optical system 70 is used (represented by a broken line in the graph), the aberration falls within the specified limit of  $0.03\lambda$  when lens surface tilt errors are within  $\pm 0.5$  minutes. It would be therefore understood that precision better than these figures are required in manufacture. Nevertheless, lens surface tilt errors less than  $\pm 0.5$  minutes are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 2$  minutes.

In contrast, if correction is made by altering the tilt of the aberration-correcting lens 72 (represented by an alternate long and short dash line in the graph), lens surface tilt errors as large as  $\pm 4.5$  minutes are tolerable. These figures are much more realistic to manufacture.

Also, if correction is made by altering both the tilt and shift of the aberration-correcting lens 72 (represented by a solid line), lens surface tilt errors as large as  $\pm 6.5$  minutes are tolerable. These figures are again much more realistic to manufacture.

Next, coma aberrations caused by a surface shift of the objective lens 71 (shift of the central axes of the two surfaces of the objective lens) are correctable by shifting or tilting either one of the aberration-



correcting lens 72 and the aberration-correcting hologram lens 73.

Figure 24 shows raw and corrected aberrations when the surface shift of the objective lens 71 contains an error within  $\pm 10 \mu\text{m}$  around the design value. The uncorrected aberration does not involve the aberration-correcting optical system 70, and the corrected aberration is obtainable as a result of altering both the tilt and shift of the aberration-correcting lens 72. It is presumed that when the objective lens 71 is molded of glass using a die as in the foregoing, the shifts of both surfaces of the objective lens 71 (lens surface shift errors) vary about  $\pm 5 \mu\text{m}$  due to die sealing and fabrication errors.

According to the graph in Figure 24, if no aberration-correcting optical system 70 is used (represented by a broken line), the aberration falls within the specified limit of  $0.03\lambda$  when lens surface shift errors are within  $\pm 3.5 \mu\text{m}$ . It would be therefore understood that precision better than these figures are required in manufacture. Nevertheless, lens surface shift errors less than  $\pm 3.5 \mu\text{m}$  are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 5 \mu\text{m}$ .

In contrast, if correction is made by altering both

the tilt and shift of the aberration-correcting lens 72 (represented by a solid line in the graph), lens surface shift errors as large as  $\pm 5.5 \mu\text{m}$  are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances  $\pm 5 \mu\text{m}$ .

Alternatively, coma aberrations caused by a surface tilt of the objective lens 71 are correctable by tilting the optical storage medium 10, for example, by tilting the axis of a motor rotating the optical storage medium 10.

Figure 25 shows raw and corrected aberrations when the surface tilt of the objective lens 71 contains an error within  $\pm 10$  minutes around the design value. The uncorrected aberration is obtainable when the optical storage medium is not inclined, and the corrected aberration is obtainable as a result of changing the inclination of the optical storage medium 10. It is presumed that when the objective lens 71 is molded of glass using a die as in the foregoing, the tilts of both surfaces of the objective lens 71 (lens surface tilt errors) vary about  $\pm 2$  minutes due to die sealing and fabrication errors.

According to the graph in Figure 25, if the optical storage medium 10 is not inclined (represented by a broken line), the aberration falls within the specified

limit of  $0.03\lambda$  when lens surface tilt errors are within  $\pm 0.5$  minutes. It would be therefore understood that precision better than these figures are required manufacture. Nevertheless, lens surface tilt errors less than  $\pm 0.5$  minutes are far from realistic to manufacture when compared to the foregoing manufacturing tolerances of  $\pm 2$ .

In contrast, if correction is made by changing the inclination of the optical storage medium 10 (represented by a solid line in the graph), lens surface tilt errors as large as  $\pm 7$  minutes are tolerable. These figures are much more realistic to manufacture than the foregoing manufacturing tolerances of  $\pm 2$  minutes.

As detailed above, the present embodiment achieves a NA as high as 0.85 with a singlet objective lens 71 by means of the inclusion of the aberration-correcting optical system 70 which corrects aberrations of the objective lens 71. The aberration-correcting optical system 70 is adapted to address errors in thickness of the objective lens 71, irregular thicknesses of the transmissive layer 8 of the optical storage medium 10, and multilayer recording, by rendering alterable the distance between the aberration-correcting lens 72 with a negative refraction power and the aberration-correcting hologram lens 73 with a positive refraction power.

Further, the aberration-correcting optical system 70 can correct coma aberrations caused by manufacturing errors of the objective lens 71 by shifting or tilting the aberration-correcting lens 72 or the aberration-correcting hologram lens 73 during assembly.

Further, the aberration-correcting hologram lens 73 can be readily fabricated with a reduced thickness, which opens a way to fabricate the aberration-correcting hologram lens 73 as an integrated part of the objective lens 71, 45° mirror, aperture, PBS, etc. If only the aberration correcting lens 72 is made movable, the optical pickup, and hence a device incorporating the optical pickup, can be further reduced in size.

A major advantage of the present embodiment the greatly reduced color aberrations by means of the provision of a diffraction lens in the aberration-correcting optical system 70. The movement of a best image point due to a variation in wavelength has improved a lot: the movement as measured per every 1 nm change in wavelength has reduced by more than 90 %, from about 0.55  $\mu\text{m}$  with the sole use of an objective lens to 0.03  $\mu\text{m}$  with the use of the aberration-correcting hologram lens 73, which is a diffraction lens, in the aberration-correcting optical system 70.

Accordingly, the best image point moves by

relatively small amounts along the optical axis, and the beam spot better stays in focus, even with an extended range of wavelength, for example, when the LD as laser emitting means oscillates in multiple mode or due to high frequency convolution. The embodiment thus address problems inherent to high density recording, such as a reduced focus depth and an accompanying need for increased accuracy in focusing the objective lens in the use of a high NA objective lens in the optical pickup: the optical system does not experience aberrations (especially, spherical and color aberrations) that add a further requirement to focusing and delivers a large focus control margin, enabling good data recording/writing.

A blaze-shaped diffraction element shown in Figure 21 has been used as the aberration-correcting hologram lens in the present embodiment so far; a diffraction element with a binary cross-section as shown in Figure 26 may be used instead. Theoretically, a 80 % or higher diffraction efficiency is available with a diffraction element having four or more levels. The overall diffraction efficiency is little affected even if the element has only two levels in some parts where as many as four levels are difficult to accommodate due to small pitches (those parts that are far from the optical axis

of the lens).

A binary diffraction element can be easily fabricated by a manufacturing process based on photolithography and therefore highly compatible with a batch process, which leads to successful production of accurate hologram lenses with high yields. Recent technology has made it possible to fabricate the blaze type by photolithography using electron beam exposure (image formation); both good diffraction efficiency and yields are obtainable. The diffraction element may be rectangular if light abounds, but preferably are of a blaze or binary type in consideration of adverse effects of noise caused by light of unrequited orders.

An optical pickup of the present invention may be such that the aberration-correcting optical system is composed of multiple elements, provided on an optical axis of the output light emitted by a light source, for either converging or diffusing the output light and is mounted so that at least one of the elements is inclinable relative to the optical axis or movable at right angles to the optical axis.

When this is the case, the projection of the output light emitted by a light source onto the objective lens becomes adjustable as at least one of the elements constituting the aberration-correcting optical system is

inclined relative to the optical axis or moved at right angles to the optical axis. Coma aberrations can be thus corrected which are due to an inclination or shift of central axes of both surfaces of the objective lens or an inclination of the objective lens to a recording face of an optical storage medium.

An optical pickup of the present invention may be such that one of the elements provided in the aberration-correcting optical system is mounted to be movable in a direction along the optical axis.

When this is the case, the convergence of the output light emitted by a light source onto the objective lens becomes adjustable as at least one of the elements constituting the aberration-correcting optical system is moved in a direction along the optical axis. Spherical aberrations can be thus corrected which are due to an error in distance between the surfaces and in surface accuracy of the objective lens.

An optical pickup of the present invention may be such that the aberration-correcting optical system corrects spherical aberrations by moving one of the elements in the aberration-correcting optical system in a direction along the optical axis, after the aberration-correcting optical system corrects the coma aberrations by inclining the elements relative to the optical axis

and moving the elements at right angles to the optical axis.

When this is the case, the aberration-correcting optical system corrects coma aberrations before spherical aberrations.

As a result, installing the optical pickup in an optical reader/writer and other devices only after coma aberrations are corrected, for example, will leave only spherical aberrations to correct when the optical reader/writer and other devices are used; no circuitry or element is required in the device to correct coma aberrations. The device is thus small in size and light in weight.

An optical pickup of the present invention may further include: aberration detecting means for detecting the coma or spherical aberrations based on a return light which is the output light reflected at the optical storage medium; and element drive means for inclining the elements relative to the optical axis and moving the elements at right angles to the optical axis to correct the coma aberrations and also for moving at least one of the elements in a direction along the optical axis to correct the spherical aberrations, all based on a detection result given by the aberration detecting means.

When this is the case, the coma or spherical



aberrations are detected, the elements are inclined relative to the optical axis and moved at right angles to the optical axis so as to correct coma aberrations, and one of the elements is moved in a direction along the optical axis so as to correct the spherical aberrations, all based on a detection result given by the aberration detecting means. This makes possible to correct coma and spherical aberrations in real time when the optical pickup is being used in the actual reading/writing of data on the optical storage medium.

Further, an optical pickup of the present invention may be such that the aberration-correcting optical system is composed of elements arranged in two separate groups, one of the two groups having a positive refraction power, the other group having a negative refraction power.

This delivers good properties by correcting aberrations due to a manufacturing error of the objective lens and compensating for effects of variations in thickness of the transmissive layer in the optical storage medium.

An optical pickup of the present invention may further include aberration detecting means and a mobile device so that the distance between the two groups provided in the aberration-correcting optical system is variable based on data given by the aberration detecting

means.

This enables multilayer recording and other types of bulk storage reading/writing by correcting aberrations due to a manufacturing error of the objective lens and compensating for effects of variations in thickness of the transmissive layer in the optical storage medium.

An optical pickup of the present invention may be such that the aberration-correcting optical system includes an aspheric lens with at least one surface.

This delivers good properties by correcting aberrations due to a manufacturing error of the objective lens and compensating for effects of variations in thickness of the transmissive layer in the optical storage medium.

An optical pickup of the present invention may be such that the group with a negative refraction power is composed of a single lens made of a material having an Abbe constant of not more than 40.

This delivers a stable servo signal and a reading signal with good characteristics with small movement of the image point even when a different wavelength enters the objective lens.

An optical pickup of the present invention may such that the aberration-correcting optical system includes achromatic doublets as the elements.

When this is the case, a stable servo signal and a reading signal with good characteristics are obtainable with small movement of the image point even when a different wavelength enters the objective lens.

An optical pickup of the present invention may such that the aberration-correcting optical system includes diffraction optical elements as the elements.

When this is the case, a stable servo signal and a reading signal with good characteristics are obtainable with little movement of the image point even when a different wavelength enters the objective lens.

An optical pickup of the present invention may such that the diffraction optical element is of either a blaze- or binary-type hologram.

When this is the case, a stable servo signal and a reading signal with good characteristics are obtainable with little movement of the image point even when a different wavelength enters the objective lens. Good manufacturability and light use efficiency also improve.

An optical pickup of the present invention may such that the objective lens is composed of a single lens.

When this is the case, the objective lens has no resin connecting part as a conventional double group lenses and as a result, delivers high resistance to temperature and humidity changes and time-related changes

and high overall reliability. Further, no fabrication is required, which readily allows for increased productivity and reduced cost. A small, lightweight, and highly rigid objective lens becomes available, which enables high density, high speed data reading/writing.

An optical pickup of the present invention may such that the objective lens is a doublet.

When this is the case, color aberrations can be reduced, high resistance to temperature and humidity changes and time-related changes, and high overall reliability become possible. High density, high speed data reading/writing also becomes available.

An optical pickup of the present invention may such that the objective lens includes a material having an index of refraction of not less than 1.75 for a wavelength actually used in the optical pickup.

This allows for a gradually sloped lens surface, which in turn makes it possible to produce objective lenses with large manufacturing tolerances.

The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art intended to be included within the scope of the

following claims.

1. A method of determining the relative humidity of a gas mixture, comprising the steps of: (a) measuring the total pressure of the gas mixture; (b) measuring the partial pressure of the gas mixture; (c) determining the relative humidity of the gas mixture from the total pressure and the partial pressure; and (d) displaying the relative humidity of the gas mixture.